HELIAN

CE ✓RoHS ♻ ⊘ ⌧

SMD3528 360LED/m DC24V

# High Efficiency LED Strip

Product Features

- Low energy consumption, high light efficiency, high quality SMD3528 LED.
- Soft and can be optionally bent to any shape with Graceful figure.
- Easy to connect and install, seamless docking, using DC24V voltage, safe and reliable.
- Good luminous brightness, soft light without glare, No spot, uniform light.
- 360LED/meter, 5meter/roll.

Applications

- Decorative lighting for exhibition shelves, advertising light box and hotel etc.
- Backlight for edge lighting / signage.
- Holiday decorative lights, residential and outdoor lighting.
- Bridge, garden, road and car lighting etc.
- Long-distance project but with inconvenient wiring.

RoHS   ETL Intertek   CE   ISO 9001 SGS

Structure & Parameter

Optocal Parameter

Model NO	HL-3R360X3528/20
Input voltage	DC24V
CRI(Ra)	≥90Ra
Power/m	28.8W/m
Lumen/led	5-7Lm/led
Color temperature	2700k/3000k/4000k/6000k
Lumen/m	2332Lm

Basic Parameter

LED Q`ty/m	360 LED/m
SMD Type	3528
Working hour	30000h
Warranty	2years
Working temperture	-20°~+45°
Minim cuttable length	16.66mm
PCB Width	20mm
Packing	5 meter/roll

⚠ Cautions

When install the led strip, please note the installation technique. The ed strip can be bent, but not distorted, as shown below.

Bend (Right)

Distortion (Wrong)

> LED strips are low votage products, you must use the power supply(transformer). Please don,t connect the led strip directly to the AC 110V or AC 220V, otherwise it will burn out the LED strips.

> Clean up the installation surface, it will ensure the reliability of the adhesive. The electrical connection process must be operated by a professional person.

Package

LED Strip   Anti-static bag

Application

H E L I A N

Professional LED strip manufacturer

Shenzhen Helian Electronics Co.,Ltd

📍 3F, Tonggao building 2, Sanlian industrial area, Songbai Rd, Shiyan Town, Bao'an District, Shenzhen, Guangdong, China

OUR EMAIL
admin@hlled.com

OUR PHONE
(86)-755-27606785

OUR WEBSITE
www.hlled.com